

Kroll Oil-fired Heater

Kroll[®]

**Heating and
Ventilating**

**Kroll's mobile range of Oil
fired heaters are ideal for
the following applications:**

Building Sites

Manufacturing Sites

Agriculture

Greenhouses

Marquees

And many others

Highly efficient –

Environmentally friendly –

Safe and easy to maintain

**Wide range of models to
every need.**

Efficient, clean and safe.





The multiple applicability of Kroll oil-fired heaters is convincing.



Oil-fired heaters with exhaust pipe

The units are suitable for closed and poorly ventilated rooms.

Type "MAK 25" oil is supplied by a compressor

| Technical Data | | MAK 25 | MA 37 | MA 55 | MA 85 |
|------------------------------|-------------------|--------|-------|-------|-------|
| Rated Heated Load | kW | 26 | 36 | 52 | 84 |
| Rated Heating Power | kW | 21 | 31,70 | 45,80 | 73,10 |
| Compressor Power | m ³ /h | 800 | 2000 | 2500 | 4500 |
| Oil consumption | kg/h | 2,20 | 2,88 | 4,16 | 6,64 |
| Electrical Power Consumption | Watt | 390 | 460 | 460 | 800 |
| Power connection | Volt | 230 | 230 | 230 | 230 |
| | Ampère | 2,0 | 3,0 | 3,0 | 6,0 |
| Exhaust pipe | Ø mm | 140 | 150 | 150 | 150 |
| Tank | Litre | 46 | 51 | 51 | 100 |
| Length | mm | 930 | 1188 | 1405 | 1680 |
| Width | mm | 560 | 620 | 620 | 690 |
| Height | mm | 625 | 790 | 790 | 938 |
| Weight | kg | 43 | 70 | 76 | 121 |
| Air outlet opening | Ø mm | - | 308 | 308 | 443 |

MA-types: suitable to connect a warm air pipe, with room thermostat and heated oil filter

Oil-fired heaters without exhaust pipe

The units are suitable for operation outdoors or in well ventilated rooms. Their efficiency is 100%.

Types "GK" oil is supplied by a compressor, and types "GP" by a high pressure pump.



| Technische Daten | | GK 20 | GK 28 | GK 40 | GP 67 | GP 115 |
|------------------------------|-------------------|-------|-------|-------|-------|--------|
| Heating Power | kW | 23 | 28 | 43 | 66 | 115 |
| Compressor Power | m ³ /h | 400 | 500 | 1050 | 2800 | 4800 |
| Oil consumption | kg/h | 1,97 | 2,37 | 3,64 | 5,22 | 9,12 |
| Electrical Power Consumption | Watt | 230 | 280 | 380 | 460 | 800 |
| Power connection | Volt | 230 | 230 | 230 | 230 | 230 |
| | A | 1,0 | 1,6 | 2,0 | 3,0 | 6,0 |
| Tank | Litre | 21 | 30 | 46 | 51 | 100 |
| Length | mm | 830 | 860 | 930 | 1405 | 1680 |
| Width | mm | 430 | 485 | 560 | 620 | 690 |
| Height | mm | 465 | 530 | 615 | 750 | 898 |
| Weight | kg | 26 | 31 | 37 | 65 | 101 |

GP-types: includes room thermostat and heated oil filter

Quality

All Kroll products are manufactured to ISO 9001.



Professionals heat with Kroll.

Technical data subject to change without notice.

Kroll GmbH · Heating and Ventilating

D-71737 Kirchberg/Murr · Pfarrgartenstraße 46
 Phone + 49 7144 830-200 · Fax + 49 7144 830-201
 Internet: www.kroll.de · E-mail: vertrieb@kroll.de